

LEAKTITE

Engineering Specification

5 Gallon 70mil Food Safe Pail**LEAKTITE PART ID: 005GFSWH020****SPECIFICATIONS**

Top Outer Diameter: 11 13/16" +/- 1/16"

Top Out of Round: 3/16" Max

Height: 14 7/16" +/- 1/16"

Wall Thickness: 70mil

Weight: 770 grams

Overflow: 5 US Gallons

← 11.872" →



14.437"

← 10.185" →

COMPONENTS

Resin: High Density Polyethylene (HDPE)

Color: White Only

Handle: 9 gauge galvanized wire injection molded no-mark plastic grip

PRINT SPECIFICATIONS

Not Available

STANDARD PACKAGING

20 per pack

Pails packed top side up

Carton 40 pounds per

6 Cartons Per Pallet = 120 bucket @ 275 pounds

Stretch Wrap: 75 guage or Higher

Wrap covers all 4 corners of the pallet.

Wrap applied with 3 full wraps at top & bottom

CORRESPONDING LIDS

Part & Description

5GLD - 5 Gallon Lid w/ Gasket

6GLD -- 5 Gallon Easy Off Lid

Color Options are available upon request

FOOD SPECIFICATION

This product meets the requirement for polyolefin resins intended for food packaging applications as described in the FDA olefin polymer regulations 21 CFR 177.1520(c)3.2(a)

The resin may be used in contact with all types of foods as defined in Table 1, 21 CFR 176.170 (c) and under conditions of use B through H as defined in Table 2, 21 CFR 176.170(c)

PALLET SPECIFICATIONS

- 1) Pallet Type: Grade "A" - 4 Way
- 2) Pallet Size: 48"x40"
- 3) Pallet Tolerance: 48"x40", +1/4"/-1/2"
- 4) Minimum Bottom Boards: 5 per - min thickness of 5/8" - min spacing 3.5"
- 5) Notching Spacing: 6"
- 6) Max Spacing on Top Deck Boards - 3.25"
- 7) Minimum Stringer Size - Width 1.5" - Height 3.5" (+ or - 1/8")
- 8) No Broken Boards in use
- 9) Deck boards must be attached with a minimum of two 11-12 gauge, 2-1/4 inch helically or annually threaded nails, staggered, per connection.
- 10) Bottom Lead & Deck Board Width - minimum of 5.5"
- 11) Top & Bottom Board Thickness - 5/8"